


1	2	3	4	5	6	7	8																						
				PRIMARY Terminal 0.250" x 0.032" 120V 50/60Hz SECONDARY Terminal 0.250" x 0.032" 24V 75VA 0V 3.2A 0.250" x 0.032"																									
				0.250" x 0.032" COM 																									
				<table><tr><td>INPUT</td><td>120V</td></tr><tr><td>OUTPUT</td><td>24V</td></tr><tr><td>MAX. VA RATING [CE]</td><td>75VA</td></tr><tr><td>FREQUENCY RANGE</td><td>50/60Hz</td></tr><tr><td>LOAD CURRENT</td><td>3.125A</td></tr><tr><td>TCO/CB</td><td>3.2A</td></tr><tr><td>WINDING INSUL. CLASS</td><td>130°C Class B</td></tr><tr><td>U.L. FILE</td><td>E214561</td></tr><tr><td colspan="2">LEAD INFO (IF USED)</td></tr><tr><td>CONDUCTOR SIZE</td><td></td></tr><tr><td>RATED TEMPERATURE</td><td></td></tr></table>				INPUT	120V	OUTPUT	24V	MAX. VA RATING [CE]	75VA	FREQUENCY RANGE	50/60Hz	LOAD CURRENT	3.125A	TCO/CB	3.2A	WINDING INSUL. CLASS	130°C Class B	U.L. FILE	E214561	LEAD INFO (IF USED)		CONDUCTOR SIZE		RATED TEMPERATURE	
INPUT	120V																												
OUTPUT	24V																												
MAX. VA RATING [CE]	75VA																												
FREQUENCY RANGE	50/60Hz																												
LOAD CURRENT	3.125A																												
TCO/CB	3.2A																												
WINDING INSUL. CLASS	130°C Class B																												
U.L. FILE	E214561																												
LEAD INFO (IF USED)																													
CONDUCTOR SIZE																													
RATED TEMPERATURE																													
				At least 5.5-point bold At least 6-point bold At least 6-point bold At least 5-point Adjust size for suitable, do not cover any content At least 5-point bold LABEL FORMAT All of content use font: Calibri 																									
				Unit: mm Tolerance  $\geq 10 \pm 1.0$ $< 10 \pm 0.2$ ZETTLER MAGNETICS A ZETTLER GROUP COMPANY Version Date Description By Drawn: Reviewed: Approved: SKU: Customer PN: Dwg No: Scale: 1:1 Page: 1/1																									
				1 2 3 4 5 6 7 8																									

