

1	2	3	4	5	6	7	8
				PRIMARY Terminal 0.250" x 0.032" 480V 50/60Hz 0.250" x 0.032" 24V 75VA 0.250" x 0.032" 0V 3.2A 0.250" x 0.032" COM			
				SECONDARY Terminal 0.250" x 0.032" 480V 50/60Hz 0.250" x 0.032" 24V 75VA 0.250" x 0.032" 0V 3.2A 0.250" x 0.032" COM			
				INPUT 480V OUTPUT 24V MAX. VA RATING [CE] 75VA FREQUENCY RANGE 50/60Hz LOAD CURRENT 3.125A TCO/CB 3.2A WINDING INSUL. CLASS 130°C Class B U.L. FILE E214561			
				LEAD INFO (IF USED) CONDUCTOR SIZE RATED TEMPERATURE			
				At least 5.5-point bold At least 6-point bold At least 6-point bold At least 5-point Adjust size for suitable, do not cover any content At least 5-point bold			
				LABEL FORMAT All of content use font: Calibri			
				Unit: mm Tolerance ≥10 ±1.0 <10 ±0.2			
				ZETTLER MAGNETICS A ZETTLER GROUP COMPANY			
				SKU: AHR75314FMQ2			
				Customer PN: ZVN-F26-0020			
				Scale: 1:1 Page: 1/1			
				Version Date Description By Drawn: Reviewed: Approved: SKU: Customer PN: Dwg No: Scale: 1:1 Page: 1/1			
				Initial release Tuan Vo Phuong Ly Khoa Huynh			
				2026/02/27 Tuan Vo Phuong Ly Khoa Huynh			
				1 2 3 4 5 6 7 8			

